

## Tube/Structural Laser Processing

## **Shapes**

- 26' In
- 26' Out
- Automated Tapping
- 1/2" Steel for production runs
- 6" Flat bar
- 4 Chuck design
- Touch Probe for centering holes
- Contour Head for bevel and miter cuts

<b>Onapos</b>	
Dimensions	Max Lbs. Per Foot
<b>Round Pipe</b> 0.79" to 8.66"	
<b>Square Tube</b> 0.79" x 0.79" 6.0" x 6.0"	26FT Max In and Out
C Channel 0.79" x 0.79" 6.0" x 6.0" "Larger size C Channel is possible, inquire for more details"	30 lbs. /ft. for maximum in feed and out feed material length.
L Channel 0.79" x 0.79" 6.0" x 6.0"	
H Beam 0.79" x 0.79" 6.0" x 6.0"	Thicker wall material
I Beam 0.79" x 0.79" 6.0" x 6.0"	can be processed if the total workpiece material weight does not exceed the
Miscellaneous Shapes	specified loading or unloading weight.
	Round Pipe 0.79" to 8.66"  Square Tube 0.79" x 0.79" 6.0" x 6.0"  C Channel 0.79" x 0.79" 6.0" x 6.0"  "Larger size C Channel is possible, inquire for more details"  L Channel 0.79" x 0.79" 6.0" x 6.0"  H Beam 0.79" x 0.79" 6.0" x 6.0"  I Beam 0.79" x 0.79" 6.0" x 6.0"